

Tiger LM 60HC

355-375 Watt

MONO-FACIAL MODULE

P-Type

Positive power tolerance of 0~+3%

IEC61215(2016), IEC61730(2016)


ISO9001:2015: Quality Management System

ISO14001:2015: Environment Management System

ISO45001:2018

Occupational health and safety management systems

Made in China/ Malaysia/ U.S/ Vietnam



MBB HC Technology

Key Features



Multi Busbar Technology

Better light trapping and current collection to improve module power output and reliability.



Reduced Hot Spot Loss

Optimized electrical design and lower operating current for reduced hot spot loss and better temperature coefficient.




Enhanced Mechanical Load

Certified to withstand: wind load (2400 Pascal) and snow load (5400 Pascal).



POSITIVE QUALITY™
Continuous Quality Assurance

LINEAR PERFORMANCE WARRANTY





12 Year Product Warranty

25 Year Linear Power Warranty

0.55% Annual Degradation Over 25 years

Engineering Drawings




Packaging Configuration

(Two pallets = One stack)

35pcs/pallets, 70pcs/stack, 910pcs/ 40'HQ Container

Electrical Performance & Temperature Dependence



Mechanical Characteristics

Cell Type	Mono PERC 166×166mm
No. of cells	120 (6×20)
Dimensions	1756×1039×30mm (69.07×40.97×1.18 inch)
Weight	21kg (46.3lbs)
Front Glass	3.2mm, Anti-Reflection Coating, High Transmission, Low Iron, Tempered Glass
Frame	Anodized Aluminium Alloy
Junction Box	IP68 Rated
Output Cables	TUV 1×4.0mm ² (+): 290mm, (-): 145mm or Customized Length
Connector	JK03M/1B, Genuine MC4
Fire rating	Class C

SPECIFICATIONS

Module Type	JKM355M-60HLM		JKM360M-60HLM		JKM365M-60HLM		JKM370M-60HLM		JKM375M-60HLM	
	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Maximum Power (Pmax)	355Wp	264Wp	360Wp	268Wp	365Wp	272Wp	370Wp	275Wp	375Wp	279Wp
Maximum Power Voltage (Vmp)	33.81V	30.75V	34.00V	31.14V	34.18V	31.36V	34.36V	31.57V	34.53V	31.70V
Maximum Power Current (Imp)	10.50A	8.59A	10.59A	8.60A	10.68A	8.66A	10.77A	8.72A	10.86A	8.80A
Open-circuit Voltage (Voc)	40.39V	38.04V	40.58V	38.22V	40.76V	38.39V	40.94V	38.56V	41.12V	38.73V
Short-circuit Current (Isc)	11.23A	9.07A	11.32A	9.14A	11.41A	9.22A	11.50A	9.29A	11.59A	9.36A
Module Efficiency STC (%)	19.52%		19.80%		20.07%		20.35%		20.65%	
Operating Temperature(°C)	-40 C ~+85 C									
Maximum System Voltage	1000VDC (IEC)									
Maximum Series Fuse Rating	20A									
Power Tolerance	0~+3%									
Temperature Coefficients of Pmax	-0.35%/C									
Temperature Coefficients of Voc	-0.29%/C									
Temperature Coefficients of Isc	0.048%/C									
Nominal Operating Cell Temperature (NOCT)	45±2 C									

*STC: Irradiance 1000W/m² Cell Temperature 25°C

NOCT: Irradiance 800W/m² Ambient Temperature 20°C

AM=1.5

AM=1.5

Wind Speed 1m/s

*Power measurement tolerance: +/-3%